



- Sony Progressive Scan CMOS sensor
- Quad Stream support
- Dual Stream, Full HD 1080P real-time + D1 real-time
- Quad Stream Compression: H.264 Baseline/Main/High Profile + MJPEG
- Remote Zoom % Focus (Motorized Lens)*
- Wide Dynamic Range
- Motion Detection
- Privacy Masks
- Smart Picture Quality / 3D Noise Reduction
- Smart IR (Option)
- Network Failure Detection
- Day/Night(ICR), Micro SD, Weatherproof, Pendant Mount Housing, Onvif


Product Specification

Item	H.264 2MP Dome Camera	
Camera		
Image Sensor	1/ 2.7" Progressive Scan CMOS	
Effective Pixels	1920 (H) x 1080 (V)	
Minimum Illumination	Color	0.2 Lux
	B/W	0.02 Lux
Shutter Speed	1~ 1/10000 sec.	
White Balance	Manual / AWB / ATW	
Lens		
Lens Type	Vari-focal / Motorized	F1.2 / f = 3 – 9 mm (ET7401Dv Vari-focal, ET7401Dm Motorized)
FOV (16:9 resolution)	103.5° (W) ~ 34.3° (T)	
Operation		
Video Compression	H.264 / MJPEG	
Video Streaming	Simultaneous H.264 1080p (25/30FPS) + MJPEG D1 (25/30 FPS)	
	Simultaneous H.264 1080p (25/30FPS) + H.264 D1 (25/30 FPS)	
Resolution	H.264	Full HD 1080p/ SXGA/ HD720p/ XGA/ SVGA/ D1/ VGA/ CIF
	MJPEG	Full HD 1080p/ SXGA/ HD720p/ XGA/ SVGA/ D1/ VGA/ CIF
Image Setting	Brightness	Manual
	Exposure	Auto / Manual
	Sharpness	Manual
	Contrast	Manual
	White Balance	Auto / Manual
	Saturation	Manual
	Hue	Manual
	Backlight Compensation	On / Off
	Digital Zoom	Support
	WDR	On / Off
	3D Noise Reduction	On / Off
	Motion Detection	On / Off
	Privacy Mask	On / Off
	Privacy Mask Type	Color
Audio	Two-way Audio	Line out, Line in / mic in
	Compression	G.711 / G.726
Alarm	Input	5V 10kΩ pull up
	Output	Photo Relay Output 300VDC / AC
Event Notification	HTTP, FTP, SMTP	
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Traditional Chinese, Russian	
Network		
Interface	10/100Mbps Ethernet (RJ-45)	
Protocol	Ipv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF	
Password Levels	User and Administrator	
Security	HTTPS, IP Filter, IEEE 802.1X	
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari	
User Account	20	
Mechanical		
Built-in IR Illumination*	Working distance	Up to 25m

Connectors	Wavelength	850nm
	Number of LEDs	24
	Power	3 pins terminal block
	Ethernet	RJ-45
	Micro SD	Micro-SDHC 32GB support
	Audio	4 pins terminal block
	Alarm In/Out	4 pins terminal block
LED Indicator	Analog Video	1.0Vp-p / 75 Ω, BNC
LED Indicator		Power, Link, ACT
General		
Operating Temperature		-10°C ~ 50°C (14°F ~ 22°F) w/ Heater & Fan, powered by DC12V: -30°C ~ 50°C (-22°F ~ 122°F) / w/ Heater & Fan, powered by AC24V: -35°C ~ 50°C (-31°F ~ 122°F) Humidity: 10 to 90; no condensation
Power Source		DC12V / AC24V / PoE
Power Consumption		System: 5W (Heater: +6W, Fan: +1W, Built-in Illumination: +3W, Motorized Lens:+3.6W)
Weatherproof Standard		IP66
Regulatory		CE, FCC, RoHS Compliant
Dimension	Indoor	Φ151 x 130mm (Φ5.9 x 5.1 inches)
	Outdoor	Φ170 x 210mm (Φ6.7 x 8.3 inches)
Weight	Indoor	0.8Kg (1.8 lbs)
	Outdoor	1.3Kg (2.9 lbs)

* Mark for optional items

IP CAMERAS ACCESSORIES In-Ceiling Mounting



Corner Mounting



Vandal Proof Fixed Dome IP Camera Outdoor Housing Kit




Vandal Proof Cover





Dimension

Indoor



Outdoor



Unit: (mm)