

EVERTECH ET-8C500L is a LAN (TCP/IP) type microprocessor resident remote alarm processing unit provides 16 supervised alarm input circuits and 16 programmable alarm output circuits which can be use in small to large systems, 256 units of remote alarm processing unit can be addressed by the MEGA-CCTV control system.

The remote alarm processing unit can be mounted near security alarm sensors at central control location, requiring simple single cable from each alarm sensor to the remote alarm processing unit,



providing full alarm reporting, sensor status monitoring and programmable alarm output control functions from the MEGA-CCTV system. These units can be used individually, or interconnected to configure an alarm network of 16 to 2048 alarm input points, supervised inputs are provided for N.C. alarm contacts for each alarm inputs. The unit requires a LAN type Cat5 (RJ45) shield data cable which connected to each remote alarm processing unit from the PC network.

The sixteen programmable alarm output control circuits which provides a open collector output (DC50V500mA), output can be used to drives alarm buzzer, audio switching, bell or relay to control low voltage device or display devices. All output points can be individual program and control by the MEGA-CCTV System computer when alarm activated and received by the MEGA-CCTV system and macro alarm output program activated.

Applications

LED communication status/LAN Status display
 DC 12V power supply for alarm sensor
 programmable 24 hour circuit
 programmable night circuit
 key switch input for system on / off recording and control
 16 zone programmable alarm output
 16 zone supervised Alarm inputs

ET-8C500L



Specifications

Component Characteristics			Communication Specifications	
Communication Ports:		One (RJ45)	Protocol:	TCP/IP UDP
alarm input zone (programmable)	24 hour		Speed	10base
	night		Transmission Distance:	100m
	key on / off		Data Cable: 4 Twisted pair, 24 AWG, shield	Cat5 Cable
alarm output circuit	programmable		Electrical Specifications	
Mechanical Specification	Height:	350mm		
	Width:	245mm		
	Depth:	80mm	Input Voltage:	AC220V
			Fuse:(Slow Blow)	2A