

MEGAsys ET-3504 Compact A4 Size 4 Ch ATM DVR

- Compact A4 Size, Best for ATM Installation
- Support Control **MEGAsys** Center
 1. Health Check—"Remote Monitor and Report DVR, Camera, HDD, and Network Connection Status"
 2. Remote Time Sync to Synchronize DVRs Time to Network Time
 3. Remote Instant Playback & Backup (Export) DVR File
 4. DVR Manager Module to Manage and Report DVR in Tree View



SPECIFICATION

		System
OS		Embedded Linux
Compression		H264/MPEG-4/MJPEG Compression
Video Format		NTSC/PAL
Video Input		4 Ch
Video Output		D Type 15 Pins VGA
Audio Input		1 Ch
Display & Recording		
Display		Splits: 1/4/ Sequencer: 1 HDD storage display Display password protection
Display Resolution		800*600
Recording Resolution	NTSC	640*480/320*240
	PAL	640*480/320*240
Recording FPS	NTSC@320*240	120
	PAL@320*240	100
Watermark		Support
Search & Playback		
Playback Channel		Max. 4 Ch SYNC playback
Playback Enhancement		De-Interlace/Sharpen
Search Mode		by Time, Date, Event and Log
Alarm		
I & O Camera Relations		1-1, 1-many, many-1, many-many
Alarm Behavior		Alarm to zoom/Alarm to recording/ Pop up message
Alarm Notice		by E-mail, FTP, SMS and Voice Dialer
Video Loss Detection		Support
Camera Mask Detection		Support
Motion to Zoom		Support

		Storage & Backup
HDD		1 internal SATA HDD (1G/1.5G)
Backup		USB/IDE burning device (CD-RW, DVD±RW) USB storage (Pen drive, HDD)
Disk Recycle Schedule		User self-defines with range from 1 to 365 days
HDD Smart Diagnosis		Support
Remote		
Networking		PPPoE, PPP, DDNS, DHCP
3G/GPRS/Wi-Fi		Support remote monitoring
Web Viewer		Max. 4 simultaneous remote clients Support remote monitoring, playback, setup, backup and reboot Max. 4 Ch SYNC playback
MEGAsys Central Management System		Connect to Max. 64 DVRs with 1024 channels Support remote monitoring, playback, setup, backup and E-MAP Max. 16 Ch SYNC playback Support multiple screen display (Max. 16)
Control Center		DVR health check, time sync and Max. 200 DVR connections
Others		
POS		Support
PTZ Control		Support
Watchdog		Built in H/W Watchdog
User Account		128 user accounts with password expiry notification Multiple levels user authority (Admin/Supervisor/User)
UI Languages		Dutch, English, French, German, Japanese, Portuguese Spanish, Simplified and Traditional Chinese
Time Sync		Support Time Server, FM and RTC time sync
Physical		
Power		100V-230V AC
Dimension		245mm(W)*249mm(D)*131mm(H)